

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 05-293788

(43)Date of publication of application : 09.11.1993

(51)Int.Cl.

B25J 19/00

B25J 17/02

F16L 39/04

H02G 11/00

(21)Application number : 04-125525

(71)Applicant : DAIHEN CORP

(22)Date of filing : 17.04.1992

(72)Inventor : MORIMOTO SHOHEI

(54) ROTARY JOINT DEVICE FOR ROBOT WRIST

(57)Abstract

PURPOSE: To prevent the occurrence of the slack, draw up, and sagging of an air hose, a control signal line, and a current collecting cable for weld, which are positioned in the vicinity of the wrist of a robot.

CONSTITUTION: A rotary joint mechanism 14 is provided for comprising a joint rotary body 12 rotated following movement of an output drive part 10 for a wrist and provided at a tip part with an attaching mount 8 for a cylinder, and a joint fixing body 13 which surrounds a part of the outer periphery of the joint rotary body 12 and integrally mounted on an output fixing part 9 for a wrist. The joint fixing body 13 is provided with an air intake port 20 to introduce air for working, a signal line lead-in port 21 through which an electric wiring 3 for transmitting a control signal is introduced, and a cable mounting part 22 to which a current collecting cable 4 for weld. Even when a wrist is widely rotated, interference of an air hose 2, protruded from the joint rotary body 12, with a peripheral device and contact of them with each other are prevented from occurring and receiving of a weld heat and spatter is reduced as low as possible.

